

# WCT3 63F LTX

12NC: 859991672920

GTIN (EAN) code: 8003437053887

Whirlpool

SENSING THE DIFFERENCE



## MAIN FEATURES

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Product group                           | абсорбатори                   |
| Colour body                             | Инокс                         |
| Material body                           | Stainless steel               |
| Colour chimney                          | Инокс                         |
| Material chimney                        | N/A                           |
| Typology                                | Built-in/Built-under          |
| Installation type                       | Built-in                      |
| Type of control                         | Electronic                    |
| Type of control settings                | -                             |
| Decor panel options                     | N/A                           |
| Motor location                          | Integrated motor in hood body |
| Operating Mode                          | Convertible                   |
| Electrical connection rating (W)        | 257                           |
| Current (A)                             | 1,12                          |
| Voltage (V)                             | 220-240                       |
| Frequency (Hz)                          | 50/60                         |
| Length of Electrical Supply Cord (cm)   | 150                           |
| Plug type                               | Schuko                        |
| Chimney height (mm)                     | -                             |
| Height of product, without chimney (mm) | 334                           |
| Height of the product                   | 334                           |
| Width of the product                    | 514                           |
| Depth of the product                    | 283                           |
| Minimum niche height                    | 0                             |
| Minimum niche width                     | 0                             |
| Niche depth                             | 0                             |
| Net weight (kg)                         | 8.6                           |

## TECHNICAL FEATURES

|                                                         |                    |
|---------------------------------------------------------|--------------------|
| Type of manual control devices                          | Touch control      |
| Type of automatic control devices                       | -                  |
| Number of motors                                        | 1                  |
| Total power of the motors (W)                           | 250                |
| Number of speed settings: boost option availability     | 4                  |
| Boost presence                                          | Yes                |
| Maximum output air extraction (m <sup>3</sup> /h)       | 550                |
| Boost position air extraction (m <sup>3</sup> /h)       | 650                |
| Maximum output recirculating air (m <sup>3</sup> /h)    | 410                |
| Boost position output recirculating (m <sup>3</sup> /h) | 430                |
| Light Control Type                                      | On/Off             |
| Number of lights                                        | 1                  |
| Type of lamps used                                      | LED                |
| Total power of the lamps (W)                            | 7                  |
| Diameter of air outlet (mm)                             | 150                |
| No-return airflow flap                                  | Yes                |
| Grease filter material                                  | Washable aluminium |
| Odour filter                                            | Yes                |

## ENERGY LABEL

|                                                 |    |
|-------------------------------------------------|----|
| Sound power at min. speed (2010/30/EU)          | 49 |
| Sound power at max. speed (2010/30/EU)          | 65 |
| Noise level with boost position (dB(A) re 1 pW) | 68 |